

SEECTOLU-CT ONLY CONSTITUTION SERIES EXIT LIGHTING



FEATURES

- Meets State of Connecticut Emergency Building Code (Para.1011.1.2)
- Rugged 20 Gauge Steel Back Box, Trim Plate and Enclosure.
- Attractive Edge-lit Design.
- Panel includes "EXIT" wording with the ADA compliant, universal wheelchair accessible symbol.
- Charge rate/power "ON" LED indicator light with Test Button.
- Maintenance-free NiCad Battery Standard.
- Recessed and Universal Surface Mount Available.
- ETL Listed 90 Minute Emergency run-time, 24 Hour Recharge.
- Meets NFPA-101 Life Safety Code.
- Exit Face is Illuminated by long-life, high intensity, Red or Green LED's.
- Universal Field Applicable Chevrons Provided.
- 120/277V Dual Primary, 60Hz Input.
- Standard Finish is White.
- 5 Year Warranty.

INTERNAL SPECS

- AC-Only and self-powered versions come standard with high-output LED technology, 120/277VAC input. Self-powered models use nickel cadmium batteries that provide a minimum 90 minutes of emergency duration. Solid state charger and transfer. All models consume 2 Watts or less nominal power.

EXTERNAL SPECS

- AC-Only and self-powered versions come standard with high-output LED technology, 120/277VAC input. Self-powered models use nickel cadmium batteries that provide a minimum 90 minutes of emergency duration. Solid state charger and transfer. All models consume 2 Watts or less nominal power.

DESIGN

- The SEECTOLU features a clean and traditional look. The indirect LED illumination evenly lights the acrylic face with crisp, even light. The clear area of the ultra thin face plate virtually disappears once installed, yet the EXIT lettering boldly distinguishes the path of egress.

LIGHT SPECS

- Illumination of the SEECTOLU is accomplished utilizing high intensity, long life red or green LEDs. LEDs provide excellent illumination while truly maximising energy efficiency. As a maintenance-free solution, LEDs provide up to 100,000 hours of use without failure.

CODES & STANDARDS

- The SEECTOLU is CSA listed and meets or exceeds the following: UL 924, NEC requirements and NFPA 101. Specifically designed to meet the requirements of the State of Connecticut Building Code Paragraph 1011.1.2, ADA Compliant.

INSTALLATION

- Install in minutes with easy to read instruction and detailed diagrams. No special hardware or tools are required.

ORDERING INFORMATION

Sample Part Number: **SEECTOLU**

MODEL	# OF FACES	OPERATION	LETTER/PANEL COLOR	MOUNTING	OPTIONS
SEECTOLU	1 - Single 2 - Double	A - AC only B - w/ Battery	RC - Red letters/clear panel RW - Red letters/white panel RM - Red letters/mirror panel GC - Green letters/clear panel GW - Green letters/white panel GM - Green letters/mirror panel	CR - Ceiling recess WR - Wall recess CS - Ceiling surface WS - Wall surface ES - End surface	SD - Self diagnostics BA - Brushed aluminum PK - Pendant kit (6" minimum) SL - Self-luminous face FAI - Fire alarm interface

NOTE: Product specifications subject to change without notice. Updated 08.2017