

SEEDLX50 PHOTOLUMINESCENT EXIT SIGN



Photoluminescent letters, maintenance free, zero energy consumption, zero cost with no lamps or battery replacement. A fully recyclable green design.

Removable chevrons standard.

Red outline shown here with optional white body.



Installation: Surface, flag, ceiling or stem mounted (hardware included). (A minimum of 5 FC of fluorescent, metal halide or mercury vapor light on the face(s) of the sign required at all times during building occupancy.)

low profile construction with consistent, uniform illumination.

indoor



SPECIFICATIONS INTERNAL

- The SEEDLX50 is 100% reliable, there are no internal parts to fail. It is a non-toxic, non-radioactive low exit solution. The SEEDLX50 is visible at up to 50 feet.

SPECIFICATIONS EXTERNAL

- Construction: ABS plastic with photoluminescent panel. The SEEDLX50 can be used for high and/or low level installations and has a 25 year life expectancy. It is visible at 50 feet during a blackout condition. The SEEDLX50 meets current building codes, NFPA Life Safety Code 101 and OSHA requirements; International Building Code 2009; International Fire Code 2009.

SPECIFICATIONS ELECTRICAL

- CIRCUIT: Since there is no electricity required, the SEEDLX50 is a safer signage solution, which saves on maintenance and energy costs.


LISTINGS AND WARRANTY

- The SEEDLX50 Series comes with a 10 to 20 year factory warranty. Deliberate damage, misuse, improper installation effectively cancel the warranty.

SPECIFICATIONS MECHANICAL

- The SEEDLX50 series utilizes photoluminescent technology which absorbs and stores ambient light. It is a non-toxic, and non-radioactive low profile emergency lighting solution. The SEEDLX50 features field adjustable chevrons and is constructed of ABS plastic with photoluminescent panel. The SEEDLX50 is NON-TOXIC and NON-RADIOACTIVE which eliminates disposal fees.

DIMENSIONS



A	B	C
8.75"	15.38"	.75"
222mm	391mm	19mm

ORDERING INFORMATION

Sample Part Number: **SEEDLX50-P2-B-UB**

SERIES	# OF FACES	FRAME COLOR	LETTER OUTLINE	MOUNTING
SEEDLX50	P1 (single) P2 (double)	R (red) G (green) B (black) W (white)[1]	G (green) R (red)	UB (universal mounting bracket)

[1]NOTE: use for outline letters (green or red) only.

[2]NOTE: only available with white frame color.

NOTE: Product specifications subject to change without notice. Updated 08.2017