



PB1: ROUND COB LED BOLLARD

HOUSING

- Extruded aluminum housing with flush mounting base & vandal-resistant screws, flat top, powdercoat finish over a chromate conversion coating, internal driver tray for easy maintenance

REFLECTOR

- Reflective white polycarbonate cone reflector

LENS

- Clear polycarbonate lens

MOUNTING

- Mounting kit with 8" anchor bolts (included).

LED

- QSSI Cool Copper COB
- Delivered Lumens: 2,282
- CRI: 80+
- CCT: 4100K
- Rated Life: 50,000 Hours
- 5-Year Warranty

WATTAGE

- COB: 20w; System 20w

DRIVER

- Electronic Driver, 120-277V, 50/60Hz
- Dimmable Driver

OPTIONS

- Surge Protection
- Custom colors available upon request
- Bollards can be cut to custom lengths upon request


WARRANTY & LISTINGS

- CSA: Listed for wet locations
- IP67




ORDERING INFORMATION: EXAMPLE: PB1C34X5U41KZSP

MODEL	LED	4X (# OF COBS)	WATTAGE	DRIVER	CCT	COLOR	OPTIONS
PB1	C3=QSSI COB	4X=4	5=5W	U=120-277V	41K=4100K	Z=BRONZE B=BLACK	SF=SINGLE FUSE DF=DOUBLE FUSE SP=SURGE PROTECTION



PROlite LED Lighting™

A Division of Emergensee® Lighting, Inc. 

TYPE: _____ DATE: _____


JOB NAME: _____

CONTRACTOR: _____


CATALOG NO: _____

NOTES: _____

OPTIONS



BOLAN



BOLRM

CATALOG #	DESCRIPTION
BOLAN4	MOUNTING KIT, INCLUDES BRACKET & (3) 4" ANCHOR BOLTS
BOLAN8	MOUNTING KIT, INCLUDES BRACKET & (3) 8" ANCHOR BOLTS
BOLAN12	MOUNTING KIT, INCLUDES BRACKET & (3) 12" ANCHOR BOLTS
BOLAN15	MOUNTING KIT, INCLUDES BRACKET & (3) 15" ANCHOR BOLTS
BOLPC	REPLACEMENT POLYCARBONATE LENS
BOLRM	ROOT MOUNT KIT

PHOTOMETRIC

