

## EasyLED Series

### EasyLED Dome Stainless Steel Bollard with Louvers



**BOLQSS**

#### Housing:

Formed 316 Stainless Steel Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance.

#### Reflector:

Cast Aluminum Louvers

#### Lens:

Clear Polycarbonate Lens

#### Mounting:

Mounting Kit with 8" Anchor Bolts (Included).

#### LumaFit LED:

Array Lumens: 2089

CRI: 83

CCT: 5000K

Rated Life: 50,000 Hours

5-Year Warranty

Aluminum Boards

#### Wattage:

Array: 14.5w, System: 17w

#### Driver:

Electronic Driver, 120-277V, 50/60Hz

Dimmable Driver

#### Listing & Ratings:

CSA: Listed for Wet Locations

#### Options:

2.5KV Surge Protection

Custom Colors Available Upon Request.

Bollards Can Be Cut To Custom Lengths Upon Request.



### EasyLED Dome Stainless Steel Bollard with Louvers

Catalog #


Description

#### Complete Units

#### Ordering Information

Example: BOLQF1X15U5KSSSP

BOL	Model:	BOL
Q	LED Mfr:	Q=QSSI
F	Optics:	F=Medium Beam Spread
1X	Number of Arrays:	1X=One
15	Wattage:	15=15w
U	Ballast:	U=120-277V
5K	CCT:	5K=5000K
SS	Color:	SS=Stainless Steel
-	Mounting:	N/A
SP	Options:	SF=Single Fuse, DF=Double Fuse, SP=Surge Protection



**BOLQSS**