



PROlite LED Lighting™

A Division of Emergensee® Lighting, Inc. 

TYPE: _____ DATE: _____

JOB NAME: _____

CONTRACTOR: _____

CATALOG NO: _____

NOTES: _____

PL-SCN-MDF032D

LED SCNCE

- Indoor Type
- LED Driver: 120V Input, Constant Current Type
- Housing: Die--form Cold-rolled Steel
- Shade: High Transmission Acrylic or Glass Creates Excellent Light Distribution and Uniformity
- LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light
- More Color Temperature Option: 3500K, 4000K
- 5 Years warranty on Driver and LED Module
- Energy Star
- Specifications



ORDERING INFORMATION

COLOR FINISH	SHADE	LED WATTAGE	LUMENS	LED COLOR TEMPERATURE	DIMENSION
SATIN NICKEL	FROSTED GLASS	16W	1150	3000K / >80	10.0" (H) x 7.2" (W) x 4.0" (D)

215-512-8100 • Fax 267-288-5604

Four Neshaminy Interplex, Suite 107, Treose PA 19053
www.proliteled.com

Specifications subject to change without prior notice.

© 2019, PROlite LED Lighting, Inc. ALL RIGHTS RESERVED