

**PROlite** LED Lighting™

A Division of Emergensee® Lighting, Inc. 

TYPE: \_\_\_\_\_ DATE: \_\_\_\_\_

JOB NAME: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_


CATALOG NO: \_\_\_\_\_

NOTES: \_\_\_\_\_

# PL-SCN-MDF076D

LED SCONCE

- Housing: Die-form Cold-rolled Steel
- LED Driver: 120V Input, Constant Current Type
- Housing: Die-form, Cold-rolled Steel
- Shade: High Transmission Acrylic or Glass Creates Excellent Light Distribution and Uniformity
- LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light
- More Color Temperature Option: 3500K, 4000K
- 5 Years warranty on Driver and LED Module
- Energy Star
- Specifications



## ORDERING INFORMATION

COLOR FINISH	SHADE	INPUT POWER	LUMENS	LED COLOR TEMPERATURE	DIMENSION
OIL RUBBED BRONZE	FROSTED GLASS	16W	1120	3000k or 4000K / >80	3.5" (H) x 8" (W) x 14.0" (L)

215-512-8100 • Fax 267-288-5604

Four Neshaminy Interplex, Suite 107, Trevoese PA 19053  
[www.proliteled.com](http://www.proliteled.com)

Specifications subject to change without prior notice.

© 2019, PROlite LED Lighting, Inc. ALL RIGHTS RESERVED