



PROlite LED Lighting™

A Division of Emergensee® Lighting, Inc.



TYPE: _____ DATE: _____

JOB NAME: _____

CONTRACTOR: _____

CATALOG NO: _____

NOTES: _____

P150WRD

LED Wrap Around

FEATURES

- **Housing**
Die-formed Cold-rolled Steel
 - **Optical**
Shade: Prismatic Acrylic
 - **Electrical**
- Lamp**
Integrated Linear LED Module



WARRANTY & LISTINGS

- **Certification**
ETL/cETL Listed

ORDERING INFORMATION

MODEL	INPUT VOLTAGE	INPUT WATTAGE	LUMENS	COLOR TEMP	CRI	SENSOR	DIMMING LEVEL	BATTERY	DIMENSIONS
Integrated LED Strips Type P150WRD-40W-830 P150WRD-40W-840	120V ~ 277V	40W	5500	3000K	80	-	-	-	46.5" x 4.12" x 3.64"
	120V ~ 277V	40W	5750	4000K	80	-	-	-	46.5" x 4.12" x 3.64"
Bi-Level Dimming with Built-in Sensor P150WRD-DIM	120V ~ 277V	40W	5500	3000K	80	HF Sensor	Dimming down to 10% ~50%	-	46.5" x 4.12" x 3.64"
Built-in Emergency Battery Back Up Type P150WRD-EM	120V ~ 277V	40W	5500	3000K	80	-	-	8W	46.5" x 4.12" x 3.64"