PROlite LED Lighting™

A Division of Emergensee® Lighting, Inc.

TYPE: _____ DATE: _____
JOB NAME: _____
CONTRACTOR: _____
CATALOG NO: _____
NOTES: _____

PFS112/PFS113

COMPOSITE OUTDOOR LIGHTING

STANDARD

LED MADE IN USA c UL us RoHS compliant ASK ABOUT ENERGY STAR

FS112

FS113

FEATURES

- Available in LED & Incandescent
- White Powder Coated Aluminum
- Wall or Ceiling Mount
- UL Listed for Wet Locations
- Standard Pack QTY: 6



EXTENDS: 4 1/4”
HCMT: 3 7/8”



EXTENDS: 4 1/2” HCMT: 5 1/4”

ORDERING INFORMATION

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FS112 FS113	**EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70* AMBIENT OP TEMP -40˚C TO +40˚C, FIVE YEAR WARRANTY, DIMMABLE, ENERGY STAR** **LE800** - 13W, 80 CRI >88 Lumens Per Watt** **W**-1140lm 3000K **C**-1280lm 4000K	**W**-White	**ACRYLIC** **C**-Clear **F**-Glare Reduced Frost Prismatic **POLYCARBONATE** **P**-Clear	N/A
	INCANDESCENT, MEDIUM BASE, 120V **I40**-1 X 40W Max	**W**-White	**ACRYLIC** **C**-Clear **F**-Glare Reduced Frost Prismatic **POLYCARBONATE** **P**-Clear	**LED LAMP, 3 YEAR WARRANTY DIMMABLE, ENERGY STAR** **LWE**-A19/E26, 80CRI, 3000K **LCE**-A19/E26, 80CRI, 4000K

(T) 267-988-4100 (F) 267-288-5604
www.EmergenseeLight.com

Specifications subject to change without prior notice.

© 2020, PROlite LED Lighting, Inc. ALL RIGHTS RESERVED