

America's Leader in Life-Safety Lighting Products

JOD Name:								
Type:								
Part #:								
Notes:								

## **SEEX LED EXIT SIGN**

## THERMOPLASTIC EXIT SIGN

STANDARD OPTIONAL

STANDARD OPTIONAL



### **ILLUMINATION**

• Ultra bright, energy efficient, long life Red or Green LEDs.

#### **ELECTRICAL**

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

#### **MOUNTING**

- EZ-snap mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

#### **HOUSING**

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- · EZ snap-out Chevron directional indicators.
- Compact, low-profile design.


# ORDERING INFORMATION

#### **OPTIONS**

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- 2C: Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplies at the same time.
- Custom: Signs available with requested 'special' wording.
- USA: Substantial transformation assembly in the U.S. complies with "Assembled in the USA" under the Buy American Act.
- cUL: Units tested to meet requirements of CAN/CSA-c22.2 No. 141-02 standard for unit equipment.

#### **WARRANTY / LISTING**

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C 50°C).
- Certified to CEC under Title 20 Regulations.



	MODEL			MODEL No. of FACES		<u>. of FACES        LETTER COLOR   HOUSING COL</u>		JSING COLOR	BATTERY		OPTIONS	
	SEEX											
•	SEEX	2	Universal Single/	R	Red	W	White	(blank)	AC-Only	SDT	Self-Diagnostics <sup>1</sup>	
			Double Face	G	Green	В	Black	EM	Battery Backup	2C	Dual Circuit Operation <sup>2</sup>	
										Custom		
										USA		
										cUL		