Emergensee® Lighting Products, Inc.

America's Leader in Life-Safety Lighting Products

Job Name:

Type:

Part #:

Notes:

SEEM3

MR-16 REMOTE CAPABLE THERMOPLASTIC EMERGENCY UNIT

STANDARD | *OPTIONAL*

ILLUMINATION

- Two fully adjustable 5.0 watt, MR-16 halogen lamp heads star
- High performance MR16 halogen lamps with smooth metallized reflector and glass lens for optimal light distribution.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- 6V maintenance-free, rechargeable sealed lead acid battery.
- Offers 10W of remote capacity (6V DC output) when using standard 5W halogen lamps and 13W of remote capacity (6V DC output) when using optional 3.3W LED lamps.
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Universal knockout pattern on back plate for wall mount. Snaps into place making internal electrical connections.
- Knockout for conduit applications.

HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

OPTIONS

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- USA: Substantial transformation assembly in the U.S. complies with "Assembled in the USA" under the Buy American Act.
- LED: 3.3W high performance MR-16 base LED lamps for increased center-to-center spacing.
- PLED: 5.0W high performance MR-16 base LED lamps for premium center-to-center spacing

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for two years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (20°C – 40°C).

DIMENSIONS



ORDERING INFORMATION

MODEL	HOUSING COLOR		OPTIONS	
SEEM3				
SEEM3	(blank)		SDT	Self-Diagnostics
	B	Black	USA	Assembled In USA
			LED	3.3W High Lumen White LED Lamps[1]
			PLED	5.0W High Lumen White LED Lamps[1]

Not available with SDT option.

Office: 215-512-8100
www.EmergenSeeLight.com

Specifications subject to change without prior notice.

© 2020, Emergensee Lighting, Inc. ALL RIGHTS RESERVED