

America's Leader in Life-Safety Lighting Products

$\sim$	h	N	2	m	16	٠.
v		IV.	ч		10	<i>,</i> .

Type:

Part #:

Notes:

# SEEHLWLEZU

Hazardous Location Exit Sign

# **OPTIONAL STANDARD**

## **ILLUMINATION**

• Ultra bright, energy efficient, long life Red or Green LEDs.

#### **ELECTRICAL**

- Dual 120/277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check-battery).
- Charge rate/power "ON" LED indicator light and magnetic test switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

#### **MOUNTING**

- Die-cast mounting brackets provided for surface wall- mount installation.
- Pre-installed conduit hub for conduit and pendant-mount installations.

#### **HOUSING**

- Housing is reinforced polycarbonate construction in gray
- Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.
- EZ snap-out Chevron directional indicators.



- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes.
- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.

#### **WARRANTY / LISTING**


**OPTIONS** 

- Five year warranty on all electronics and housing. Batteries
- pro-rated for five years.
  Meets UL924, UL844, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes.
- P66 rated for Ingress Protection.
  Rated for Class 1, Division 2, Groups A,B,C,D.
  UL listed for wet locations (-20°C 50°C).
- Certified to CEC under Title 20 Regulations.

## **ELECTRICAL INFORMATION**

CATALOG NUMBER	INPUT W	ATTS (W)	INPUT AMPS (A)		
CATALOG NUMBER	120			277V	
SEEHLWLEZU-RED/GREEN/EM/SDT	3.0	3.0	0.03	0.02	

# **DIMENSIONS**



#### ORDERING INFORMATION

MODEL	No. of FACES		o. of FACES LETTER COLOR		HOUSING COLOR BATTERY		ATTERY	OPTIONS		
SEEHLWLEZU					G	Gray				
	1 2	Single Double	R G	Red Green			, ,	AC-Only NiCd Battery		Self-Diagnostics Temper Proof