

**Job Name:**

**Type:**

**Part #:**

**Notes:**

## SEELEDM7W

### RECESSED LED EMERGENCY UNIT

STANDARD



## ILLUMINATION

- Two fully adjustable 1.0W white LED lamp heads.
- High performance chrome-plated metal reflectors and plastic lens for optimal light distribution.

## ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- 6V maintenance-free, rechargeable sealed lead acid battery.
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

## MOUNTING

- Bar hangers on the back box for recessed mount.
- Compatible with drop ceiling mount installations.

## HOUSING

- Durable 20-gauge steel trim plate in white or black finish.
- Trim securely attached to housing with spring clips.

## ORDERING INFORMATION

MODEL	HOUSING COLOR
SEELEDM7W	
SEELEDM7W	W - White B - Black



## LISTINGS AND WARRANTIES

- Five year warranty on all electronics and housing. Battery pro-rated for two years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for dry locations (25°C).

## DIMENSIONS

