

Job Name: _____
Type: _____
Part #: _____
Notes: _____

SEENYEXDC

NEW YORK APPROVED LED DIE CAST ALUMINUM EXIT SIGN

STANDARD



OPTIONAL

ILLUMINATION

- Ultra bright, energy efficient, long life red LEDs.
- New York City compliant 8" EXIT letters.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Aluminum mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

HOUSING

- Premium-grade, aluminum housing (also available in optional black or white powder-coated finishes).
- Field selectable knockout Chevron directional indicators.
- Unique design allows double face conversion in the field.
- Quick-snap face plate closure.

ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
SEENYEXDC	5.0	5.0	0.041	0.018

ORDERING INFORMATION

MODEL	No. of FACES	HOUSING COLOR	FACE PANEL	BATTERY	OPTIONS	
SEENYEXDCR						
	1	Single Face	W White	W White	(blank) AC-Only	SDT Self-Diagnostics ¹
	2	Double Face	B Black	B Black	EM Battery Backup	2C Dual Circuit Operation ²
	3	Universal Single/Double face	A Aluminum	A Aluminum		

¹ Available only with EM units.

² Available only with AC units.



OPTIONS

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- 2C: Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplies at the same time.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C – 50°C).
- Certified to CEC under Title 20 Regulations.

DIMENSIONS

