

**Job Name:** \_\_\_\_\_

**Type:** \_\_\_\_\_

**Part #:** \_\_\_\_\_

**Notes:** \_\_\_\_\_

# SEENYEX

## NEW YORK APPROVED APPROVED LED EXIT SIGN



### FEATURES

- Heavy duty steel construction
- NY approved housing with steel knockout chevron directional indicators
- UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

### ELECTRICAL

- Dual 120V/277V voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- Long-life, maintenance-free, rechargeable NiCad battery (EM model)
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours

### MOUNTING

- Universal mounting canopy & hardware included for top, side, or end-mount installation

### HOUSING

- Durable, white powder coated, 20-gauge steel construction
- Universal K/O chevrons

### ORDERING INFORMATION



### ILLUMINATION

- Ultra-bright, energy efficient, long-life Red LED
- NY approved 8" EXIT letters

### WARRANTY & LISTINGS

- Five Year Warranty on all electronics and housing. Batteries are pro-rated warranted for 5 years.

### DIMENSIONS



Sample Part Number: SEENYEX-2-R-W

MODEL	# OF FACES	LETTER COLOR	HOUSING COLOR	BATTERY
SEENYEX		R		
SEENYEX	1 - SINGLE FACE 2 - DOUBLE FACE 3 - UNIVERSAL SINGLE/DOUBLE	R - RED	W - WHITE B - BLACK	BLANK - AC ONLY EM - NICAD BATTERY