

Job Name: \_\_\_\_\_

Type: \_\_\_\_\_

Part #: \_\_\_\_\_

Notes: \_\_\_\_\_

## GLASS CHIMNEY COLLECTION




### SPECIFICATIONS

- 120V INPUT VOLTAGE, 50/60Hz
- HIGH POWER FACTOR
- AMBIENT OPERATING TEMPERATURE -40°C (-40°F) TO +50°C (122°F)
- ESTIMATED 50,000 HRS L
- 5 YEAR WARRANTY
- DIMMABLE
- ACRYLIC DIFFUSER
- STANDARD PACK QTY: 1
- MOLDED OF DURABLE NON-CORROSIVE UV RESISTANT RESINS
- POST TOPS FIT MOST 3 INCH DIAMETER POSTS (NOT INCLUDED)
- UL LISTED FOR WET LOCATIONS



**PFT271**

SHOWN WITH OPTIONAL GLASS CHIMNEY




SHOWN WITH OPTIONAL GLASS CHIMNEY



**PFT171**

SHOWN WITH OPTIONAL GLASS CHIMNEY



EXTENDS: 10 1/4" HCMT: 15"

### ORDERING INFORMATION

| STYLE #        | SOURCE/WATTAGE   | LUMENS/CCT                                | BODY                   | LENS                                  | OPTIONS                                     |
|----------------|--|---|------------------------|---------------------------------------|---|
| PFT271 = POST  | LE800 = 13W POWER INPUT<br>CRI = 80 (TYP)<br>>65 LUMENS PER WATT** | W = 900lm<br>3000K<br>C = 1000lm<br>4000K | B = BLACK<br>W = WHITE | C = CLEAR<br>W = WHITE<br>F = FROSTED | G = GLASS CHIMNEY FROSTED<br>T = BRASS TRIM |
| PFT171 = SHORT | LE800 = 13W POWER INPUT<br>CRI = 80 (TYP)<br>>65 LUMENS PER WATT** | W = 900lm<br>3000K<br>C = 1000lm<br>4000K | B = BLACK<br>W = WHITE | C = CLEAR<br>W = WHITE<br>F = FROSTED | G = GLASS CHIMNEY FROSTED<br>T = BRASS TRIM |

| LE800 LED REPLACEMENT PARTS |                          |
|-----------------------------|--------------------------|
| L08-AC120R-W                | = 900 LUMEN 3000K ARRAY  |
| L08-AC120R-C                | = 1000 LUMEN 4000K ARRAY |

\* DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

\*\* ESTIMATED FROM LED SOURCE