

**PDC012**  
**Ceiling Fixture**

**Features**

**Housing**

Die-formed Cold-rolled Steel  
 Finish Option: -62 Satin Nickel, -01 Polish Brass, -06 White, -30 Oil Rubbed Bronze

**Optical**

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

**Electrical**

High Power Factor, Low THD  
*Built-in Emergency Lighting*  
*Bi-level Lighting*

**Lamp**

Built-in LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light.  
 Color Temperature Option – 3000K, 3500K, 4000K, 5000K

**Certifications**

ETL/cETL Listed, Energy Star

**Warranty**

5 Years Warranty on Driver and LED Module



**Emergency Backup Models**

Model	Input Voltage	Input Wattage	CRI	Lumen (TYP) / CT	Dimension (OD X H)	Energy Star
PDC012D-2G-D-xxxxK-EM	120V	18W	> 80	1430 / 3000K	11.8" x 5.0"	Yes
PDC014D-2G-D-xxxxK-EM	120V ~ 277V	23W	> 80	2267 / 3000K	14.6" x 5.7"	Yes
PDC016D-2G-D-xxxxK-EM	120V ~ 277V	28W	> 80	2600 / 3000K	16.0" x 5.9"	Yes
PDC018D-2G-D-xxxxK-EM	120V ~ 277V	35W	> 80	3364 / 3000K	17.7" x 5.9"	Yes

**Bi-level Lights with Built-in High Frequency Sensor**

Model	Input Voltage	Input Wattage	CRI	Lumen (TYP) / CT	Dimension (OD X H)	Energy Star
PDC012D-2G-D-xxxxK-BI	120V	18W	> 80	1430 / 3000K	11.8" x 5.0"	Yes
PDC014D-2G-D-xxxxK-BI	120V ~ 277V	23W	> 80	2267 / 3000K	14.6" x 5.7"	Yes
PDC016D-2G-D-xxxxK-BI	120V ~ 277V	28W	> 80	2600 / 3000K	16.0" x 5.9"	Yes
PDC018D-2G-D-xxxxK-BI	120V ~ 277V	35W	> 80	3364 / 3000K	17.7" x 5.9"	Yes

**Bi-level Lights with Emergency Backup**

Model	Input Voltage	Input Wattage	CRI	Lumen (TYP) / CT	Dimension (OD X H)	Energy Star
PDC012D-2G-D-xxxxK-EM-BI	120V	18W	> 80	1430 / 3000K	11.8" x 5.0"	Yes
PDC014D-2G-D-xxxxK-EM-BI	120V ~ 277V	23W	> 80	2267 / 3000K	14.6" x 5.7"	Yes
PDC016D-2G-D-xxxxK-EM-BI	120V ~ 277V	28W	> 80	2600 / 3000K	16.0" x 5.9"	Yes
PDC018D-2G-D-xxxxK-EM-BI	120V ~ 277V	35W	> 80	3364 / 3000K	17.7" x 5.9"	Yes