

# SEECEM

## Reduced Profile All LED Exit & Emergency Thermoplastic Combo

### ILLUMINATION:

- Ultra-bright, energy efficient, long-life Red or Green LED EXIT sign illumination.
- Selectable Red/Green (RG) version available. See ordering matrix below.
- Ultra-bright, energy efficient, long-life White LED adjustable LED lamp heads provide up to 30-ft center-to-center spacing with 3-ft path of egress at 10-ft mounting height.
- 1.5 watt (3 LEDs x 0.50 watt) per head.
- Unique all-inclusive lamp, reflector and lens assembly.

### ELECTRICAL:

- Dual 120/277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery).
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 3.6V long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

### MOUNTING:

- Mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

### HOUSING:

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- Snap-out Chevron directional indicators.

### OPTIONS:


- RC: Remote capacity of 2.5 watts.
- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes. Universal 120-277 voltage.
- USA: Substantial transformation assembly in U.S. complies with "Assembled in USA" under the Buy American Act.

### WARRANTY / LISTING:

- Five-year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C – 50°C).
- Certified to CEC under Title 20 Regulations.



### DIMENSIONS



### ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
LSCM RED/GREEN	1.2	1.2	0.12	0.11
LSCM RED/GREEN RC	1.2	1.2	0.12	0.11
LSCM RED SDT	2.7	2.7	0.32	0.32
LSCM GREEN SDT	2.4	2.4	0.29	0.29
LSCM RED/GREEN RC SDT	3.0	3.0	0.40	0.40

### REMOTE LAMP COMPATIBILITY

MODEL NUMBER	BATTERY	REMOTE CAPACITY	COMPATIBLE REMOTE HEAD FAMILY			
			RHLED	MRHLED	RH16LED	SRHLED
LSCM RC	3.6V	2.5W	x	x		

### STANDARD



### OPTIONAL



## ORDERING INFORMATION

Sample Part Number: **LSCMRW**

MODEL	No. of FACES	LETTER COLOR		HOUSING COLOR		OPTIONS	
SEECM	Universal Single/ Double Face	R	Red	W	White	RC	Remote Capacity
		G	Green	B	Black	SDT	Self-Diagnostics <sup>2</sup>
		RG	Red/Green			USA	Assembled in USA

<sup>2</sup> Not available with RG units.