

**Job Name:** \_\_\_\_\_

**Type:** \_\_\_\_\_

**Part #:** \_\_\_\_\_

**Notes:** \_\_\_\_\_

# SEEM6WL

## MR-16 WET LOCATION SEMI-RECESSED POLYCARBONATE EMERGENCY UNIT

STANDARD | OPTIONAL



### ILLUMINATION

- Two fully adjustable, semi-recessed ultra bright, 7.2 watt MR-16 halogen lamp heads standard.
- High performance MR16 halogen lamps with smooth metallized reflector and glass lens for optimal light distribution.

### ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- 6V maintenance-free, rechargeable sealed lead acid battery.
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

### MOUNTING

- Universal knockout pattern on back plate for wall mount. Snaps into place making internal electrical connections.

### HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in gray or black finish.
- Fully gasketed clear polycarbonate cover offers protection against wet, non-hazardous dust, corrosive atmospheres and to water spray or splashing water locations.

### WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for two years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for wet locations (20°C – 40°C).

### ORDERING INFORMATION

| MODEL   | HOUSING COLOR |               | WP |              | OPTIONS                         |   |
|---------|---------------|---------------|----|--------------|---------------------------------|---|
| SEEM6WL |               |               |    |              |                                 |   |
| SEEM6WL | (blank)<br>B  | Gray<br>Black | WP | Wet Location | CW<br>USA<br>LED<br>PLED<br>CEC | Internal Heater With Battery Blanket<br>Assembled IN USA<br>3.3W High Lumen White LED Lamps<br>5.0W High Lumen White LED Lamps <sup>1</sup><br>Title 20 Compliant |



### OPTIONS

- HTR: Optional internal heater for cold temperature (-9°C – 40°C) applications.
- CW: Optional internal heater and battery blanket for extreme cold temperature applications, (-25°C – 50°C MR-16 halogen) (-25°C – 40°C LED).
- USA: Substantial transformation assembly in the U.S. complies with "Assembled in the USA" under the Buy American Act. LED: 3.3W high performance MR-16 base LED lamps for increased center-to-center spacing.
- CEC: Certified to CEC under Title 20 Regulations.
- PLED: 5.0W high performance MR-16 base LED lamps for premium center-to-center spacing.

### DIMENSIONS

