

PHBL-LKFS

Lumen and Kelvin Field
 Selectable Linear Highbay

STANDARD



FEATURES

- Field selectable 4000k (neutral white) and 5000k (cool white) color temperatures.
- Patent-safe LEDs provide at least 100,000 hours of operation with at least 70% of initial lumen output (L_{70}).
- Tri-lumen selectable luminaire delivers 12,000 to 60,000 lumens and 135 lumens per watt.
- Sensor ready.
- Medium distribution is standard with optional narrow distribution and wide distribution.
- Universal 120-277 AC voltage (50-60Hz) is standard.
- 0-10vdc dimming drivers are standard.
- Color rendering index > 80.
- Painted steel housing and PMMA (polymethyl methacrylate) lenses are standard.
- Chain-mount kits (includes v-hooks and 1/8" thick, 1 meter long chain) are standard.
- Options include wire-guard kits, pendant mount kits, and surface mount kits.



WARRANTY & LISTINGS

- cULus listed for damp locations in ambient temperatures from -40°C to 50°C (-40°F to 122°F).
- DLC 5.1 premium approved for medium distribution.
- DLC 5.1 standard approved for wide and narrow distributions.
- Complies with FCC Part 15, class A.
- 5-year warranty on all electronics and housing.

MOUNTING OPTIONS

- Chain mounting with V-hooks is standard.
- Optional pendant mounting kit provides pendant attachment to 1/2" rigid conduit.
- Optional surface mounting kit provides attachment to solid surfaces.

DIMENSIONS (inches)

Model	L (in)	W (in)	H (in)
18L	16.5	10.25	1.75
24L	23	10.25	1.75
36L	31	10.25	1.75
60L	44	10.25	1.75

ORDERING INFORMATION

Example: PHBL-24L-LKFS

Model	Nominal Lumen Output (Selectable)		Kelvin Selectable		Input Voltage		Emergency Driver ¹		Accessories	
	18L	24L	LKFS	4000k/5000k	UNC	347-480V	EM5	No emergency driver	HD07VR-MH	Microwave occupancy sensor
	24L	36L			Blank	120-277V	EM10			
	36L	60L					EM13			
	60L						Blank			

¹ Emergency drivers available for 120-277V models only.