



**ORDERING INFORMATION**

Model	Size	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
PETH-PL14405W5C	1x4	(15W, 20W, 25W, 30W, 40W)	120-277V	0.14A@120V, 0.06A@277V 0.18A@120V, 0.08A@277V 0.23A@120V, 0.10A@277V 0.28A@120V, 0.12A@277V 0.37A@120V, 0.16A@277V	1950 2600 3250 3900 5200	130 lm/W	(3500K, 4000K, 5000K, 5700K, 6500K)	0-10V	White	47.80"L x 11.90"W x 1.38"H
PETH-PL22405W5C	2x2	(15W, 20W, 25W, 30W, 40W)	120-277V	0.14A@120V, 0.06A@277V 0.18A@120V, 0.08A@277V 0.23A@120V, 0.10A@277V 0.28A@120V, 0.12A@277V 0.37A@120V, 0.16A@277V	1950 2600 3250 3900 5200	130 lm/W	(3500K, 4000K, 5000K, 5700K, 6500K)	0-10V	White	23.70"L x 23.70"W x 1.38"H
PETH-PL24505W5C	2x4	(25W, 30W, 35W, 40W, 50W)	120-277V	0.23A@120V, 0.10A@277V 0.28A@120V, 0.12A@277V 0.32A@120V, 0.14A@277V 0.37A@120V, 0.16A@277V 0.46A@120V, 0.20A@277V	3250 3900 4550 5200 6500	130 lm/W	(3500K, 4000K, 5000K, 5700K, 6500K)	0-10V	White	47.80"L x 23.70"W x 1.38"H
PETH-PL24725W5C	2x4	(30W, 40W, 50W, 60W, 72W)	120-277V	0.28A@120V, 0.12A@277V 0.37A@120V, 0.16A@277V 0.46A@120V, 0.20A@277V 0.55A@120V, 0.24A@277V 0.66A@120V, 0.29A@277V	3900 5200 6500 7800 9360	130 lm/W	(3500K, 4000K, 5000K, 5700K, 6500K)	0-10V	White	47.80"L x 23.70"W x 1.38"H

Mount	Emergency
<b>PETH-SM14</b> Surface Mount Kit 1x4	<b>EM8</b> [INSTALLED] Emergency LED Driver, 8W, 90-Min Battery
<b>PETH-SM22</b> Surface Mount Kit 2x2	<b>EM20</b> [INSTALLED] Emergency LED Driver, 20W, 90-Min Battery
<b>PETH-SM24</b> Surface Mount Kit 2x4	

**SPECIFICATIONS**

<p><b>ENERGY DATA</b></p> <p><b>Input Voltage:</b> 120-277V</p> <p><b>Input Frequency:</b> 50/60 Hz</p> <p><b>Wattage:</b> 5-Wattages (40W Max, 50W Max, 72W Max)</p> <p><b>Power Factor:</b> &gt;0.9</p> <p><b>Total Harmonic Distortion (THD):</b> &lt;15%</p> <p><b>Operating Temperature:</b> -4°F to 113°F (-20°C to 45°C)</p>	<p><b>LIGHTING DATA</b></p> <p><b>Lumens:</b> 1950 to 9360</p> <p><b>Lumens Per Watt:</b> 130 lm/W</p> <p><b>Correlated Color Temperature (CCT):</b> 5-CCT (35K, 40K, 50K, 57K, 65K) <b>Dimmable:</b> 0-10V</p> <p><b>Color Rendering Index (CRI):</b> 83</p> <p><b>L70:</b> 50000 hours</p>
---	--

**PHYSICAL DIMENSIONS**

