

PLR201 Series

Wrap Around Surface Mount Units

STANDARD



This surface mounted wrap around unit is designed for use in most commercial, residential, and institutional type applications. The unit provides maximum light output with minimum clearance.



Construction:

- Housing is designed from heavy gauge die formed steel and is finished in baked white enamel or polyester powder coating for maximum durability and reflectivity. Clear acrylic prismatic wrap around diffuser hinges from either side and snaps on and off for easy maintenance.

Electrical

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location M 59006648


Mounting

Unit is equipped with knockouts and holes for pendant or surface mounting. This Fixture can be mounted individually or continuous run.

WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location M 59006648

DIMENSIONS



Fixture Length

T12	T8	T5	Length
F20T12	F17T8	F14T5	24"
F40T12	F32T8	F28T5	48"
F96T12	F96T8	---	96"

For Tandem Units:

Multiply lamp length above by lamp quantity

Fixture	Bulb Spacing
2 Tube	5 3/8"
4 Tube	2 1/4" - 5 3/8"
2-Tube HO	7"
4 Tube Housing	

max weight= 16lbs/48" 32lbs/96"

Ordering Guide

PLR201

Series

of Lamps

Lamp Size

Ballast Type

Options

PLR201

1 = 1 lamp

2 = 2 lamp

3 = 3 lamp

4 = 4 lamp

T8

T5

17 = F17T8

14 = F14T5

25 = F25T8

21 = F21T5

32 = F32T8

28 = F28T5

59 = F96T8

86 = F96T8/HO

TSHO

24 = F24T5

39 = F39T5

T12

54 = F54T5"

15 = F15T12

20 = F20T12

30 = F30T12

40 = F40T12

96 = F96T12

96HO = F96T12/HO

SET LED N = Wired 1 end hot for LED tubes

SET LED N/S = Wired 2 ends hot for LED tubes

W/LEDIF = LED ballast driven tubes

EMB = emergency ballast

2BAL = 2 ballast

REFS = Silver Reflecto

OCC-E = External Occupancy Sensor